

# Ablative Antifouling

General purpose antifouling

## PRODUCT DESCRIPTION

Ablative Antifouling is a general purpose antifouling designed to provide good antifouling protection for up to one season. Suitable for all vessel types except for aluminium.

## PRODUCT INFORMATION

<b>Product Code</b>	NAU751 - Red, NAU753 - Blue, NAU754 - Black
<b>Typical Shelf Life</b>	2 years
<b>VOC (as supplied)</b>	400 g/lit
<b>Unit Size</b>	4 lit

## DRYING/OVERCOATING INFORMATION

	Drying			
	5°C (41°F)	15°C (59°F)	23°C (73°F)	35°C (95°F)
Touch Dry	1 hr	45 mins	30 mins	20 mins
Immersion	24 hrs	12 hrs	6 hrs	3 hrs

**Note:** Max. Immersion Times are as follows: 5-15 °C - 3 mths; 23 °C - 2 mths; 35 °C - 1 mth

Overcoated By	Overcoating Ambient / Substrate Temperature							
	5°C (41°F)		15°C (59°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max
Ablative Antifouling	16 hrs	Ext	10 hrs	Ext	6 hrs	Ext	4 hrs	Ext

## APPLICATION AND USE

<b>Preparation</b>	<p><b>PREVIOUSLY ANTIFOULED SURFACE</b>  <b>In Good Condition:</b> Rinse with fresh water and allow to dry. If old antifouling is incompatible or unknown, seal with Nautical Underwater Primer.  <b>In Poor Condition:</b> Remove all antifouling then follow priming instructions.</p> <p><b>PRIMING</b> For all preparation of unprimed surfaces use Nautical Underwater Primer.</p> <p><b>BARE GRP / STEEL / IRON / LEAD / WOOD</b> use Nautical Underwater Primer</p>
<b>Application Methods</b>	<p><b>Mixing</b> Stir well before use.  <b>Cleaner</b> Nautical NT2  <b>Ventilation and Humidity Control</b> Apply in dry, well ventilated conditions.  <b>Spray application</b> - PROFESSIONAL USE ONLY.</p>
<b>Some Important Points</b>	Do not use below 5°C.
<b>Number of Coats</b>	2 coats per season. 3 coats are required on the leading and trailing edges, waterline, rudder and keel.

# Ablative Antifouling

General purpose antifouling

<b>Recommended DFT</b>	80 microns dry
<b>Recommended WFT</b>	167 microns wet
<b>Application Methods</b>	Brush, roller
<b>Coverage</b>	(Theoretical) - 6 m <sup>2</sup> /lt by brush (Practical) – 5.4 m <sup>2</sup> /lt by brush

## TRANSPORTATION, STORAGE AND SAFETY INFORMATION

### Storage

#### GENERAL INFORMATION

Exposure to air and extremes of temperature should be avoided. For the full shelf life of the product to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight.

#### TRANSPORTATION

The product should be kept in securely closed containers during transport and storage.

### Safety

#### GENERAL

Read the label safety section for Health and Safety Information.

#### DISPOSAL

Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of this product cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

### IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*